



Light is vision.

# V-Lux 1000

The V-Lux is a low-Cost and compact cold light source. Durable and reliable for industrial applications.



## Features and Benefits

- 20V/150W
- Constant Color Temperature
- Continous Intensity Adjustment
- Use of EKE or DDL Bulbs
- Long Lamp Life
- Low Noise/Vibration

## Technical Specifications

Average lamp life (average of continous operation)	DDL : 1.000h
Average lamp life (average of continous operation)	EKE : 675h
Fuse transformer	Integrated, resettable
Color temperature	DDL: 3100K
Color temperature	EKE: 3150K
Mechanical light adjustment	Crescent Shaped Diaphragm
Noise level	25dB(A)
Housing temperature	98°F
Dimensions (H x W x D)	4.25"x6.875"x8.25"
Weight	9 lbs.
Housing	Light gray metal



Light is vision.

## Variants

Product	Part No.
V-Lux 1000 USA/CDN 120V	14363
V-Lux 1000 EURO 230V	14364

## Accessories

Product	Part No.
<b>Spare Lamp</b>	
EKE Lamp 21V/150W Halogen For Intralux® 5100, 5/6000-1, dc-1100, V-Lux, NCL 150	13695
DDL Lamp DDL Lamp for Intralux 5/6000-1 / NCL 150 / V-Lux 1000, 20V/150W	23500.014
EPV Lamp EPV Lamp for Intralux 4000-1, 14.5V/900W	23829.025
<b>Metal Standard/GZ6 Ringlight</b>	
Metal Standard/ GZ6 Ringlight Mounting diameter 66mm, working distance 30-150mm, 28" flexible length (other lengths available).	14909
<b>Meiji EMZ/Nikon SMZ/Olympus SZX</b>	
Meiji EMZ/Nikon SMZ/Olympus SZX Mounting diameter 60mm, working distance 30-150mm, flexible length 28"	14743
<b>Gooseneck Light Guide Twin Arm</b>	
Gooseneck Light Guide Twin Arm, 5.4mm fiber x 500mm length	25301
Gooseneck Light Guide Twin Arm, 4.7mm fiber x 500mm length	14425
<b>Foot Switch</b>	
Foot Switch For IntraLED 2020, Halogen Light Sources and LED Ringlights (plug and play).	60197.000



Light is vision.

**Product**

**Part No.**